SECTION 1. IDENTIFICATION

Product identifier used on the la	abel	
:	Trailer Brightener	
Other means of identification :	00356, 00357, 00358	
Recommended use of the chem	ical and restrictions on use	
		ner Name, address, and telephone number of the supplier: Refer to manufacturer
117 West Tupper Street Buffalo, NY, USA 14201		
Manufacturer's Telephone # : 24 Hr. Emergency Tel # :	1-800-735-3773 Chemtrec 1-800-424-9300 (With (Outside U.S.).	in Continental U.S.); Chemtrec 703-527-3887

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Blue liquid. Acrid odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification

Acute Toxicity, oral - Category 2 Acute toxicity (dermal) -Category 1 Acute toxicity, inhalation - Category 2 Eye Damage/Irritation - Category 1 Skin Corrosion/Irritation - Category 1

Label elements

Hazard pictogram(s)



DANGER!

Hazard statement(s)

Fatal if swallowed. Fatal in contact with skin. Fatal if inhaled. Causes severe skin burns and eye damage.

Precautionary statement(s)

Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Do not breathe mist or vapor. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves/clothing and eye/face protection.

Immediately call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification: Corrosive to respiratory system Contact with most metals will generate flammable hydrogen gas.

Enviromental Precautions: See Section 12 for more environmental information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	Common name and synonyms	<u>CAS #</u>	Concentration (% by weight)
Hydrofluoric acid	Fluoric acid	7664-39-3	10.0 - 30.0
Sulfuric acid	Vitriol oil	7664-93-9	3.0 - 7.0
2-butoxyethanol	Ethylene glycol monobutyl ether butyl cellosolve Glycol Ether EB EGBE	111-76-2	1.0 - 5.0
Quaternary ammonium compounds, (hydrogenated tallow alkyl) bis(hydroxyethyl) methyl, ethoxylated, chlorides	PEG-15 Hydrogenated Tallowmonium Chloride	68187-69-9	1.0 - 5.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Μ

e. Do NOT induce vomiting. Never give erson. If breathing has stopped, give artificial
xygen by qualified medical personnel only.
е.
ninated clothing. Immediately flush skin with 20 minutes. Seek immediate medical
er for at least 20 minutes. Seek immediate
age. Corrosive to the eyes and may cause

Causes severe skin burns and eye damage. Corrosive to the eyes and may cause severe damage including blindness. Direct skin contact may cause corrosive skin burns, deep ulcerations and possibly permanent scarring. Fatal if swallowed, in contact with skin or if inhaled.

Indication of any immediate medical attention and special treatment needed

: Immediate medical attention is required.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Dry chemical, carbon dioxide and foam.

Unsuitable extinguishing media

: Do not use water. May react with water.

Special hazards arising from the substance or mixture / Conditions of flammability

: Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

: Non-flammable.

Hazardous combustion products

: Carbon oxides; Sulphur oxides; Hydrogen fluorine gas; formaldehyde; irritating fumes and smoke.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

: Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus.Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.
 Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.
 Methods and material for containment and cleaning up
 Ventilate area of release. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. In case of acid solution, neutralize with excess soda ash or sodium bicarbonate, mix and scoop up slurry. Wash residual with water. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and

spilled product. Contact the proper local authorities.

Special spill response procedures

 In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
 US CERCLA Reportable quantity (RQ): Hydrofluoric acid (100 lbs / 45.4 kg); Sulfuric acid (1000 lbs / 454 kg)

equipment to avoid static accumulation. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Conditions for safe storage	:	Use in a well-ventilated area. Wear suitable protective equipment during handling. Do not ingest.Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flames. Keep away from combustible material. Avoid contact with incompatible materials. Wash thoroughly after handling. Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.
Incompatible materials	:	Strong bases, Strong oxidizing agents, Strong reducing agents, Metals, Water , Arsenic oxides, Phosphorus pentoxide, Vinyl acetate, Ammonia, Ethylenediamine, Perchlorates, Potassium permanganate, Sodium Hydroxide , Halogens , Acetylides, Alkalies.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:				
Chemical Name	ACGIH	<u>rlv</u>	<u>OSHA</u>	PEL
	TWA	<u>STEL</u>	PEL	<u>STEL</u>
Hydrofluoric acid	0.5 ppm (F)	N/Av	3 ppm (F)	N/Av
Sulfuric acid	0.2 mg/m³ (thoracic fraction)	N/Av	1 mg/m³	N/Av
2-butoxyethanol	20 ppm	N/Av	50 ppm (240 mg/m³) (skin)	N/Av
Quaternary ammonium compounds, (hydrogenated tallow alkyl) bis(hydroxyethyl) methyl, ethoxylated, chlorides	N/Av	N/Av	N/Av	N/Av

Exposure controls

Ventilation and engineering measures

· • · · · · · · · · · · · · · · · · · ·	
	: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof electrical and ventilating equipment. In case of insufficient ventilation wear suitable respiratory equipment.
Respiratory protection	: If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.
Skin protection	: Wear protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye / face protection	: Chemical splash goggles must be worn when handling this material. A full face shield may also be necessary.
Other protective equipment	: Wear resistant clothing and boots. Other equipment may be required depending on workplace standards. An eyewash station and safety shower should be made available in the immediate working area.
General hygiene consideration	ons
	: Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Odour	: Acrid odor.
Odour threshold	: N/Av
рН	: 1.0
Melting Point/Freezing point	: N/Av
Initial boiling point and boilin	g range
0.1	: N/Av
Flash point	: N/Ap
Flashpoint (Method)	: N/Ap
Evaporation rate (BuAe = 1)	: N/Av
Flammability (solid, gas)	: N/Ap
Lower flammable limit (% by	vol.)
	: N/Av
Upper flammable limit (% by	vol.)
	: N/Av
Oxidizing properties	: None known.
Explosive properties	: Not explosive
Vapour pressure	: N/Av
Vapour density	: N/Av
Relative density / Specific gra	avity
	: 1.02 - 1.253
Solubility in water	: Soluble
Other solubility(ies)	: N/Av
Partition coefficient: n-octane	ol/water or Coefficient of water/oil distribution
	: N/Av
Auto-ignition temperature	: N/Av
Decomposition temperature	: N/Av
Viscosity	: N/Av
Volatiles (% by weight)	: 100 (as water and acid)
Volatile organic Compounds	
	: N/Av
Absolute pressure of contain	er
	: N/Ap
Flame projection length	: N/Ap
Other physical/chemical com	ments
	: No additional information.
SECTION 10. STABILITY A	ND REACTIVITY
Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous read	tions
	Hazardous polymerization does not occur.
Conditions to avoid	: Avoid heat and open flame. Ensure adequate ventilation, especially in confined areas. Avoid contact with water.
Incompatible materials	: See Section 7 (Handling and Storage) for further details.
Hazardous decomposition pr	
· ·	: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation	:	YES
Routes of entry skin & eye	:	YES
Routes of entry Ingestion	:	YES

Routes of exposure skin absorption

: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

0 1 1	
Oise and assessed as a first state	Harmful or fatal if inhaled. Inhalation of high concentrations of fumes or mists may cause severe irritation and corrosive damage to the nose, throat and upper respiratory tract. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness. Could result in pulmonary edema (fluid accumulation). Symptoms of pulmonary edema (chest pain, shortness of breath) may be delayed.
Sign and symptoms ingestio	n
	 Harmful or fatal if swallowed. Causes severe irritation, swelling, corrosive burns and damage in mouth and throat. May be absorbed and cause symptoms similar to those for inhalation.
Sign and symptoms skin	: Corrosive to skin. Causes severe burns, symptoms may be delayed. May be absorbed and cause symptoms similar to those for inhalation.
Sign and symptoms eyes	: Corrosive to eyes. Chemical burns, corneal damage, and possibly blindness can result from direct contact. May be absorbed and cause symptoms similar to those for inhalation.
Potential Chronic Health Effe	
	: Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Repeated or prolonged exposure may result in kidney effects. In extreme cases, tooth erosion could result. Prolonged exposure may cause skeletal fluorosis (weakened bone structure).
Mutagenicity	: Not expected to be mutagenic in humans.
Carcinogenicity	No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP. IARC has classified "strong inorganic acid mists containing sulphuric acid" as a known carcinogen (IARC category 1). This classification does not apply to this product; it only applies to mists containing sulphuric acid, and not to sulphuric acid or sulphuric acid mixtures.
Reproductive effects & Terat	
	: Not expected to cause reproductive effects.
Sensitization to material	Not expected to be a skin or respiratory sensitizer.
Specific target organ effects	
Medical conditions aggravat	
	: Pre-existing skin, eye, respiratory and central nervous system disorders.
Synergistic materials	: Not available.
Toxicological data	: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

	LC₅₀(4hr)	LD	150
<u>Chemical name</u>	<u>inh, rat</u>	(Oral, rat)	(Rabbit, dermal)
Hydrofluoric acid	655 ppm	N/Av	N/Av
Sulfuric acid	255 mg/m³	2140 mg/kg	N/Av
2-butoxyethanol	450 ppm (2.175 mg/L) (vapour)	530 mg/kg	400 - 500 mg/kg
Quaternary ammonium compounds, (hydrogenated tallow alkyl) bis(hydroxyethyl) methyl, ethoxylated, chlorides	N/Av	N/Av	N/Av

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: No data is available on the product itself.

Ecotoxicity data:

Ingredients	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Hydrofluoric acid	7664-39-3	48 Hr LC50 Leuciscus idus: 660 mg/L	N/Av	N/Av
Sulfuric acid	7664-93-9	96 Hr LC50 Brachydanio rerio: >500 mg/L [static]	N/Av	N/Av
2-butoxyethanol	111-76-2	1490 mg/L (Bluegill sunfish)	> 100 mg/L (Zebra fish)	None.
Quaternary ammonium compounds, (hydrogenated tallow alkyl) bis(hydroxyethyl) methyl, ethoxylated, chlorides	68187-69-9	N/Av	N/Av	N/Av

Ingredients	CAS No	Toxicity to Daphnia			
		EC50 / 48h	NOEC / 21 day	M Factor	
Hydrofluoric acid	7664-39-3	48 Hr EC50 Daphnia species: 270 mg/L	N/Av	N/Av	
Sulfuric acid	7664-93-9	24 Hr EC50 Daphnia magna: 29 mg/L	N/Av	N/Av	
2-butoxyethanol	111-76-2	835 mg/L (Daphnia magna)	100 mg/L	None.	
Quaternary ammonium compounds, (hydrogenated tallow alkyl) bis(hydroxyethyl) methyl, ethoxylated, chlorides	68187-69-9	N/Av	N/Av	N/Av	

Ingredients	CAS No	Toxicity to Algae					
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor			
Hydrofluoric acid	7664-39-3	N/Av	N/Av	N/Av			
Sulfuric acid	7664-93-9	N/Av	N/Av	N/Av			
2-butoxyethanol	111-76-2	911 mg/L/72hr (Green algae)	286 mg/L/72hr	None.			
Quaternary ammonium compounds, (hydrogenated tallow alkyl) bis(hydroxyethyl) methyl, ethoxylated, chlorides	68187-69-9	N/Av	N/Av	N/Av			

Persistence and degradability

: No data is available on the product itself.

Bioaccumulation potential

: No data is available on the product itself.

<u>Components</u>	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Hydrofluoric acid (CAS 7664-39-3)	-1.4	no bioaccumulation
Sulfuric acid (CAS 7664-93-9)	-2.20(estimated)	no bioaccumulation
2-butoxyethanol (CAS 111-76-	2) 0.8	0.97
Mobility in soil :	No data is available on the product itself.	
Other Adverse Environmental	effects	
:	The ecological characteristics of this product have product should not be allowed to enter drains or wa it can affect ground or surface waters.	
SECTION 13. DISPOSAL CO	NSIDERATIONS	
Handling for Disposal	Handle waste according to recommendations in Se residue (liquid and/or vapour) and can be dangero or near this container. Dispose of in accordance with federal, provincial a	us. Do not cut, weld, drill or grind on
RCRA :		e United States, it may meet the RA, Title 40 CFR 261. It is the the proper waste identification and

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
IMDG	UN3264	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrofluoric and sulfuric acid)	8	II	
IMDG Additional information	Consult the IMI	DG regulations for exceptions.	-		
ICAO/IATA	UN3264	Corrosive liquid, acidic, inorganic, n.o.s. (Hydrofluoric and sulfuric acid)	8	II	IF R
ICAO/IATA Additional information	Refer to ICAO/	ATA Packing Instruction	<u> </u>		v
TDG	UN3264	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydorfluoric and sulfuric acid)	8	II	
TDG Additional information	May be shipped exceeding 30 k	d as LIMITED QUANTITY when transported in containers g gross mass.	no larger than '	1.0 Litre, in p	backages not
49CFR/DOT	UN3264	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrofluoric and sulfuric acid)	8	II	
49CFR/DOT Additional	May be shipped exceeding 30 k	d as LIMITED QUANTITY when transported in quantities r g gross mass.	io larger than 1	Litre, in pac	kages not

according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>		TSCA	CERCLA Reportable	SARA TITLE III: Sec. 302, Extremely	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical		
	CAS #	Inventory	Quantity(RQ) (40 CFR 117.302):	Hazardous Substance, 40 CFR 355:	Toxic Chemical	de minimus Concentration	
Hydrofluoric acid	7664-39-3	Yes	100 lb/ 45.4 kg	100 lb TPQ	Yes	0.1%	
Sulfuric acid	7664-93-9	Yes	1000 lb/ 454 kg	1000 lb TPQ	Yes	0.1%	
2-butoxyethanol	111-76-2	Yes	None.	None.	No	N/Ap	
Quaternary ammonium compounds, (hydrogenated tallow alkyl) bis(hydroxyethyl) methyl, ethoxylated, chlorides	68187-69-9	Yes	N/Ap	N/Av	No	N/Ap	

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Health hazards (Acute toxicity; Eye Damage; Skin corrosion). Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	Californ	State "Right to Know" Lists						
		Listed	Type of Toxicity	СА	MA	MN	NJ	PA	RI
Hydrofluoric acid	7664-39-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Sulfuric acid	7664-93-9	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
2-butoxyethanol	111-76-2	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Quaternary ammonium compounds, (hydrogenated tallow alkyl) bis(hydroxyethyl) methyl, ethoxylated, chlorides	68187-69-9	No	N/Ap	No	No	No	No	No	No

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:

Trailer Brightener SDS Preparation Date (mm/dd/yyyy): 03/05/2019

SAFETY DATA SHEET

Ingredients	CAS #	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Hydrofluoric acid	7664-39-3	231-634-8	Present	Present	(1)-306	KE-20198	Present	HSR001537, HSR001568, HSR001569, HSR001570, HSR001589 (dilution)
Sulfuric acid	7664-93-9	231-639-5	Present	Present	(1)-724; (1)-430	KE-32570	Present	HSR001572, HSR001573, HSR001588 (dilution)
2-butoxyethanol	111-76-2	203-905-0	Present	Present	(7)-97; (2)-407	KE-04134	Present	HSR001154
Quaternary ammonium compounds, (hydrogenated tallow alkyl) bis(hydroxyethyl) methyl, ethoxylated, chlorides	68187-69-9	N/Av	Present	Present	N/Av	KE-30031	Present	May be used as a component in a product covered by a group standard, but is not approved for use as a chemical in its own right.

SECTION 16. OTHER INFORMATION

Legend

Legend	: ACGIH: American Conference of Governmental Industrial Hygienists CAS: Chemical Abstract Services CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 CFR: Code of Federal Regulations DOT: Department of Transportation EPA: Environmental Protection Agency HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank IARC: International Agency for Research on Cancer Inh: Inhalation MSHA: Mine Safety and Health Administration N/Ap: Not Applicable N/Av: Not Available NFPA: National Fire Protection Association NIOSH: National Institute of Occupational Safety and Health NTP: National Toxicology Program OSHA: Occupational Safety and Health Administration PEL: Permissible exposure limit RCRA: Resource Conservation and Recovery Act RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act STEL: Short Term Exposure Limit TDG: Canadian Transportation of Dangerous Goods Act & Regulations TLV: Threshold Limit Values TPQ: Threshold Planning Quantity TSCA: Toxic Substance Control Act TWA: Time Weighted Average WHMIS: Workenbook Hazardoux Materials Identification System
References	 WHMIS: Workplace Hazardous Materials Identification System 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2018. 2. International Agency for Research on Cancer Monographs, searched 2018. 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2018 (Chempendium, HSDB and RTECs). 4. Material Safety Data Sheets from manufacturer. 5. US EPA Title III List of Lists - March 2015 version. 6. California Proposition 65 List - November 23, 2018 version. 7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2018.

Preparation Date (mm/dd/y	уууу)
Other special consideratio	-
HMIS Rating	 Provide adequate information, instruction and training for operators. <u>*- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe</u> Health: 0 Flammability: 0 Reactivity: 0
NFPA Rating	0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe : Health: 0 Flammability0 Instability:0 Special Hazards: 0
Prepared for: FPPF Chemical Company, 117 West Tupper Street Buffalo, NY, USA 14201 Telephone: 1-800-735-377 Please direct all enquiries t	
Prepared by: ICC The Compliance Center Ir Telephone: (888) 442-9628 (U http://www.thecompliance	J.S.): (888) 977-4834 (Canada)

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from FPPF Chemical Company, Inc and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and FPPF Chemical Company, Inc.

END OF DOCUMENT